



香港賽馬會  
The Hong Kong  
Jockey Club

# Practical Turf Management – 5<sup>th</sup> Seminar Renovation of the Hong Kong Stadium Pitch

**Mr. Pako P C Ip**  
**Executive Manager, Tracks**  
**The Hong Kong Jockey Club**  
**6 June 2015**

# Contents

- Review of profile performance before renovation
- Site investigation & irrigation audit
- Perched water construction design: terrain, drainage
- Gravel, sand, reinforcing agent, organic amendment selection
- Irrigation system design
- Quality Management Program: Turf Nursery, Quarry
- Construction technology
- Current Progress


# HVRC Tunnel Construction July 2014



## 2. Sampling and tests Oct 2013

- 15 sampling sites around the pitch
  - especially high wear areas
- To view roots and profile
- 

N




## 2. Sampling and tests

- A list of tests were commenced to draw the conclusion
- Testing Root Zone Material
  - Particle size & shape analysis
  - Saturated hydraulic conductivity
  - Moisture release curve & retention
  - Air filled porosity
  - Organic matter Profile
- Testing Gravel
  - Particle size analysis
  - Hydraulic conductivity
  - Gravel suction influence on the sands moisture retention
  - Migration compatibility









### 3. Profile Study

AS BUILT



- Top Dark Layer 50mm to 130mm in thickness
- Grey Sand Layer 0mm to 150mm in thickness
- Orange/ Mesh Layer from 50 to 250mm from the grass surface. This over laid a lower Orange/Lower Sand only layer. The overall thickness of these two layers ranged between 200mm to 300mm
- Crushed Granite Gravel 48mm to 125mm
- 65mm Subsoil Drainage Lateral Pipe System at 0.38% slope and 3m spacing
- Existing Subgrade - found some road base but mainly appeared a gravelly clay material


EXISTING PROFILE



Major issue: non uniform drainage

The overall thickness of the root zone above the gravel ranged from 350mm to 490mm

## 2. Profile Study - Top Dark Layer (Result of poor maintenance)




- ✗ Silty sand containing **3.0 % - 9.4 %** organic matter
- ✗ Very poor drainage (**1mm - 40mm/hr.**) & water can't infiltrate this layer
- ✗ Variable depths (50mm - 130mm in thickness, ave 99mm)
- ✗ Foul (anaerobic) smell for some samples
- ✗ Extended time to dry the profile after rain
- ✗ Cut up easily during play in wet
- ✗ Difficult to develop sustainable deep roots
- **Initial thought - this top silty sand layer material should be removed**






### 3. Profile Study - Gravel Drainage Layer



- ✓ Hydraulic conductivity of the gravel: 252,768mm/hour (low for a gravel of this size range)
- ✗ Variable thickness: 48mm -125mm, ave 88.7mm

### 3. Profile Study – Drainage evaluation



- ✓ each side of the field drain over 100mm/hour (white dots)
- ✗ center of the field drains at 18mm/hour (yellow dots)
- Design range should be at least 150mm/hr.
- Note- Lateral drainage system is inadequate for the Hong Kong climate



## 4. Summary and Suggestions

### Prior study recommendation

Remove the top dark layer only

- Back to the surface stability and dryness problems experienced in the as built profile
- Quick fix without addressing other defects underneath
  - Do not address poor drainage
  - Unstable surface in long dry season

### Current recommendation

- Full reconstruction
- But – requires a package solution
  - Rectify problems with proper solutions in line with international stadium standards
  - Continuous and professional turf monitoring system
  - Contract ready to use turf
  - Grow light (to improve growth under shade)
  - Fans installation (to improve ventilation)
  - Skilled and qualified people

# Geotechnical Investigation Nov 2014



HKJC - Racing Operations

# Base Examination Dec 2014




HKJC - Racing Operatio

# Hong Kong Stadium Irrigation Audit

Date: 6/1/2015-7/1/2015



# Can Test



**9.53      Precipitation rate (mm/Hr)**

**CU    57.9%**

**DU    32.5%**

**SC    3.1**



Late Dr. V. I. Stewart

How far do we understand how it  
works ?

Could we not do better?


June 1970

# Design Criteria

- capacity to handle 150mm/hr rain fall event.
- growing medium profile that supports deep healthy roots and healthy shoot growth
- provides the moisture retention for optimum stability and playability.
- provides for rapid recovery after usage.
- To have a grass selection that best suites the climate for the usage requirements.

# Perched Water Table Reinforced Profile

Reinforced




# Surface Slope

Needed to fit to rubber surrounds an goal post sleeves levels while still producing sufficient grade for the drainage and some surface drainage.



Grades placed into 3D total station layout in order to laser grade all pavement layers to the pitch surface grades and to the tolerances required.

# Drainage Layout



# Drainage System Design Concepts

- Main drain with double lining pipe of various sizes to provide the rigidity with little resistance for water flow
- Lateral system connected to main drain pipes surrounding the edge of the pitch
- Main drain discharge at the south and north curvet
- Save cutting rubber pavers
- Design to cope with 150mm of rainfall per hour

# Drainage Pipe Layout



Lateral  
connections  
at 4m centres



450mm @ 2%

250mm @ 0.5%  
300mm @ 0.5%  
375mm @ 0.5%

# Sub soil drain pipe



New Sub soil drain pipe  
Spacing: 4m apart



Old sub soil drain pipe  
Spacing: 3m apart

## Gravels and Sand Selected

- Gravel F - to be used for the gravel drainage layer and the lateral pipe backfill.
- Gravel 10mm - to be used as a bridging gravel over 15mm gravel.
- Gravel 15mm – to be used around all main line pipes.
- Sand F – to be used for all growing medium layers.

# Migration test – materials preparation




# Gravel F Particle Size Analysis and D90 and D15 Determinations



Ground Science  
ACN 105 704 078  
13 Brock Street Thomastown VIC 3074, P (03) 9454 4617 F (03) 9454 4618

## Particle Size Analysis



D15	1.955
D90	5.791
sieve size mm	% retained
9.5mm	0.0
6.7mm	0.0
4.75mm	23.6
2.36mm	56.1
1.18mm	19.5
600um	0.4
425um	0.0
300um	0.0
150um	0.1
75um	0.0
Pan	0.3

# Further Gravel Testing

Migration testing of F gravel on 10mm gravel.  
No migration occurred.



150mm lateral pipe tested for migration of gravel F if placed around pipes. Pipe covered in gravel and then vibrated and shaken with and without water applications. No migration of gravel entered into the pipe through the perforations.




# Particle Size Analysis and D15 and D85

## of the sand



ACN 105 704 078

13 Brock Street Thomastown VIC 3074, P (03) 9464 4677 F (03) 9464 4658




sieve size mm	% retained
D15	0.179
D85	0.487
sieve size mm	% retained
6.7	0.0
4	0.0
2.8	0.0
2.000	0.0
1.000	1.4
0.500	11.4
0.250	57.7
0.150	22.2
0.053	6.9
Pan	0.4

**Moisture Content %**  
 1.9

# Moisture Release Curve Testing

At the proposed depth of the growing medium of 250mm plus the gravel suction (68mm), the moisture release curve indicates a moisture retention of 15 % by volume.


This is too low and needs an organic amendment to assist in lifting this to a higher level.



# Gravel Grading and Migration compatibility



Ground Science  
ACN 005 704 078  
13 Brock Street Thomastown VIC 3074, P (03) 9464 4617 F (03) 9464 4618



SAMPLE No.	#2 GRAVEL F	ROOTZONE SAND	#5 SAND F
% Passing	Sieve size(mm)		
100	9.5		
100	6.7		
76.4	4.75		
20.3	2.36		
0.8	1.18		
0.4	0.800		
0.4	0.425		
0.4	0.3		
0.3	0.15		
0.3	0.075		
90	5.791		
15	1.955		

Bridging Migration Factor with sand = 4.01

Uniformity Factor with sand = 2.96

# Migration Compatibility

- The 15% passing diameter of the gravel must not be more than 7 times the diameter of the 85% passing diameter of the overlying growing medium.

$$D_{15} \text{ (gravel)} < 7 \times D_{85} \text{ (growing medium – bridging factor)}$$


The gravel must also have a uniform particle size:

- The 90% Passing diameter of the gravel must not be more than 3 times the 15% passing diameter of the gravel.

$$D_{90} \text{ (gravel)} < 3 \times D_{15} \text{ (gravel - uniformity factor)}$$

# How the Perched Water Table is Formed

A meniscus is formed by the water held on the sand particles over the gravel air space that is broken by forming a head pressure of water above the gravel in the sand.




A water reserve is created by the gravel in the layer above.

This will maintain an even moisture in the above sand layer over the whole pitch.



# How the Perched Water Table can be made ineffective

The meniscus is not formed by the sand migration into the gravel.



# Maintaining Perched Water Table During Installation



It is important to maintain a sharp interface between the gravel and the sand above and to maintain some moisture in the sand and gravel to ensure the perched water table is achieved during the installation.

# Reinforcements supplied as additives in construction that are generally added by specific equipment are:

Reflex (Netlon) mesh elements



Desso Grassmaster

# StaLok




# Loksand



# Mesh Element Reinforcement

- Product developed in 1982.
- Research undertaken by Strathclyde University and Texas A&M University.
- Used in Happy Valley Racecourse in 1988 & utilized in stadia and racecourses globally
- Assist drainage, resist compaction, provide consistent firmness, stabilize sand profile



# Peat Moss Amendment



Mainly used to provide better moisture retention, root hair production and some additional stability to the sand.


# Moisture Retention and Hydraulic Conductivity of the Mixture

RESULTS SUMMARY					
 Ground Science SPORTS FIELDS					
ACN 105 704 078 13 Brock Street Thomastown VIC 3074, P (03) 9464 4617 F (03) 9464 4618					
Client:	HONG KONG JOCKEY CLUB			Job No.	G2783
Project:	STADIUM PITCH RENOVATION			report ref	AZ
Location:	HONG KONG			issued by:	EG
				date	19/03/2015
sample No.		# 9 SAND F 12% PEAT	# 9 SAND F 12% PEAT		
sample id:		t/m <sup>3</sup>	%		
Bulk dry density of test specimen			22.2	22.2	
Initial Moisture content			23.5	-	
Temperature of water			POTABLE	-	
Water type			840	-	
Saturated Hydraulic conductivity @ 16 drops of 150mm compacted at bulk density		mm/hr	1.342	-	
		t/m <sup>3</sup>	650	-	
Saturated Hydraulic conductivity @ 32 drops of 150mm compacted at bulk density		mm/hr	1.378	-	
pH 5:1 water			-	-	
Suction height	mm	335	315		
Specific Gravity		2.65	2.65		
volumetric water content		19.59	21.93		
Wet density	t/m <sup>3</sup>	1.558	1.655		
Gravimetric Water content	%	14.4	15.3		
Dry Bulk Density	t/m <sup>3</sup>	1.362	1.436		
TOTAL POROSITY	%	48.6	45.8		
Capillary Porosity	%	19.59	21.93		
Air fill porosity	%	29.0	23.9		

Hydraulic conductivity = 650mm/hr  
at a bulk density of 1.378t/m<sup>3</sup>

At a suction of 315mm, a specific gravity of 2.65 and at a wet bulk density of 1.655 t/m<sup>3</sup> the mixture provides:

- A total porosity of 44.93%.
- A moisture retention of 21.93% by volume.
- An air filled porosity of 23.0%



# Irrigation pipe



UPVC 100 (old)




HKJC - Racing Operations




PE100 [PN16] (new)


# Valve Under Head Arrangement



# Irrigation Pump Assembly




# Computer Irrigation Controller



# Profile Performance Influences

- To provide a consistent surface in all weather conditions.
- The factors that most influence surface performance are weather, usage, grass density and quality, maintenance, profile composition and its moisture retention and drainage.
- Maintaining healthy roots and low thatch will be critical to maintain the performance



# Late Dr. V. I. Stewart

What could go wrong :

unscientific design

inefficient workmanship

inadequate supervision

inappropriate maintenance

1994

# Quality Control Witness and Hold

HONG KONG NATIONAL STADIUM PITCH RECONSTRUCTION							
Witness Inspections & Hold Points							
Witness Inspection No.	Hold Point	Works Description	Representative Responsible	Principal Contract Administrator	Consultant Approved	checked & Supplied	Inspection Date
1	Turf farm inspections						
2	Gravel production						
	1 Gravel production testing by supplier				gbs		
	2 Gravel delivery testing by HKJC				gbs		
3	Sand production						
	3 Sand production testing by supplier				gbs		
	Sand delivery testing by HKJC				gbs		
4	Excavation, coke removal & coke sealcoat ends						
5	Subgrade formation						
	4 Subgrade firmness				gbs	25Ayr	
	5 Subgrade level tolerance survey				gbs	25Ayr	

# Quality Control : Material

- On Turf Farm
- On Quarry Plant
- On Stadium Site
- At Happy Valley Lab

# ITGAP Farm (Fuzhou)



25/5/2015

# ITGAP Farm (Fuzhou) information summary

- **Genetically pure foundation stock imported in 2013**
- Plant quarantine infra-structures
- Site Isolation fence
- Pre plant media fumigation
- Cleaning facility before nursery entry
- 5 m vegetation free zone
- Quality water supply and highly sandy rootzone



Sod cutting



Before wash: around 20-30mm root zone layer



Washing the sod by hose



After wash: Very good stolon, rhizome content



# Reviewing turf packing & post harvest handling



# Duomen Factory inspection



Gravel & Sand production




# Production line inside factory



## Finished product – on site PSD tests



# PSD tests in Happy Valley laboratory






Raw materials of 15-20 mm gravels



Final product of 15-20mm gravel




# Construction Technologies & Site Progress



# Laser Levele



# Field Top Maker



ing Operations



# Sand mesh mix production commences



# Drainage performance under the black rain storm




# Latest Site Progress



# Program Summary

## HK STADIUM- PITCH RECONSTRUCTION WORKS 2015

### WORK MONITORING PROGRAMME (Updated on 3/6/2015)



# Risk



# Risk

“Sorry, but cannot do. Please find another supplier. ”

# Acknowledgement

- Mr. Peter Semos, Managing Director, Global Turf Solutions Pty Ltd
- Mr Ernie Gmehling, Managing Director, GroundScience
- Mr TY Cheung, Tracks Manager
- Mr Ray Cheng, Tracks Officer
- Ms Kiki Lau, Assistant Tracks Officer



# Thank You !

